



CRYSTALS

CRISTAL BARICOTE

TECHNICAL SHEET

CEMENT-BASED SHRINKAGE-CONTROLLED PRODUCT FOR WATERPROOFING CONCRETE STRUCTURES THROUGH INTERNAL CRYSTALLISATION.

CRISTAL BARICOTE is a quick-setting mortar, waterproof, specifically designed to repair cracks, holes and joints.

CRISTAL BARICOTE contains special ingredients that react chemically with concrete forming millions of needle-like hydration crystals. These crystals grow and enter deeply into the widespread porosity of the mortar and surrounding concrete, blocking the passage of water.



Use

- Repairing cracks, joints and holes in concrete.
- Grouting spacers and formwork boards.
- Repairing chipping and cracks in concrete.
- Creating a waterproof plaster on brickwork.

Advantages and benefits

- It's waterproof. Contains active crystals.
- Contains no corrosive agents or metals.
- Accelerated hardening, high initial compression strength.
- It is suitable for drinking water.
- It can be painted over.
- It is shrinkage-controlled.

Application methods

- The concrete or brick surface must be compact and clean.
- Saturate the substrate with water, avoiding leaving free water.
- Mix **CRISTAL BARICOTE** in a ratio of 4 parts powder to 1 part clean water (by volume).
- Apply by trowel. Do not exceed 13 mm thickness per coat. For greater thicknesses mix with 10 mm gravel (pea gravel).
- **CRISTAL BARICOTE** develops considerable hydration heat during setting: protect against dehydration by spraying water on the surface.

WARNINGS

- Do not use below 5°C and above 35°C.
- Protect from rain, dehydration and frost during curing.

Dosage

1 kg of powder mixed with the required water yields 430 dm³ of mortar.

Technical Data

Colour :	Grey
Specific Weight :	1.8 Ton/m ³
Appearance:	Powder
Workability :	60' at 20°C
Exposure Class :	XF4, XA1L
Compressive strength:	at 1 day approx. 7.5 N/mm ² at 3 days approx. 20 N/mm ² at 7 day approx. 35 N/mm ² at 28 days approx. 40 N/mm ²



SYSTEM[®]
TECHNOLOGY

WATERPROOFING
TECHNOLOGIES

www.ital-systemtec.it
info@ital-systemtec.it



CRYSTALS

CRISTAL BARICOTE

Conservation

Store in a dry place.
Open pails are subject to deterioration if exposed to moisture.

Health Warnings

R-phrases:

R 36 : Irritant to eyes
R 38 : Irritant to skin
R 43 : Sensitisation possible through skin contact

S-phrases:

S 2: Keep out of reach of children
S 24: Avoid contact with skin and eyes
S 25: In case of contact with the eyes, wash immediately with plenty
of water and consult a doctor
S 28: In case of contact with the skin, wash immediately with
plenty of water
S 37: Use suitable gloves

Disposal according to Ö S 2100:31601

Packaging

25 kg plastic pail

All information is given in good faith and without any warranty. The application, use and processing of these products are beyond our control and therefor your responsibility. Any eventual established liability, through bad application or any other reason, for any damages, is always limited to the values of the goods supplied by System Technology.
The products and systems are manufactured under total quality management.



SYSTEM[®]
TECHNOLOGY

WATERPROOFING
TECHNOLOGIES

www.ital-systemtec.it
info@ital-systemtec.it